

# Aerosmith High Pressure Structural Steel and Concrete Pins



HN120



**When the Pressure is High...**

**Try Aerosmith Pins with your High Pressure Tools**



Wood to Concrete  
Drywall to Concrete  
Wood to Steel



The **FASTEST** way to penetrate concrete.

- ↓ Powerful enough to drive .300" head pins into concrete
- ↓ Easily fasten subfloor, underlayment and sleepers to concrete
- ↓ 2x4 to Red Iron Steel and Concrete
- ↓ 16 ga Heavy Track to I-Beam and Concrete
- ↓ Shortens job time and increases profits
- ↓ Ultra Light tool weighs only 6.4 lbs.
- ↓ Free of Powder Load
- ↓ Low Recoil
- ↓ Adjustable magazine plate to allow 1"-2-1/2" pin accommodation
- ↓ No Licensing Required

Call 1-800-528-8183 or visit us online at [www.AerosmithFastening.com](http://www.AerosmithFastening.com).

An **aerosmith**® Product...

**Defining the Standard for Steel & Concrete Fastening**

Aerosmith Fastening Systems  
5621 Dividend Road, Indianapolis, IN 46241  
Ph: 317.243.5959 Fax: 317.390.6980  
Email: [info@AerosmithFastening.com](mailto:info@AerosmithFastening.com)  
[www.AerosmithFastening.com](http://www.AerosmithFastening.com)



Aerosmith pins ensure consistent and durable fastening.



# Use Aeromsmith Pins in Your High Pressure Tools

Aeromsmith has pins for your High Pressure tools. Aeromsmith .145HP pins are designed to attach Hardwood Floor underlayment, 2x4 to Red Iron steel and Concrete and 16ga Heavy Steel Track to I-Beam/Concrete

## .145 Series, Knurled and Smooth Shank Plastic Sheet Coil Collated

Design Loads  
LGSRG-2-96

LARR  
RR22668  
RR25264

ICC / ICBO  
ER-5667

ER-5001  
ESR-1799

ITEM	LENGTH	KNURL	CARTON	APPLICATION	
5253HP	1" (25mm)	SMOOTH	1.5 M	STEEL TRACK	CONCRETE
5323HP	1-1/4" (32mm)	SMOOTH	1.5 M	PLYWOOD	CONCRETE
5323HPG	1-1/4" (32mm)	SMOOTH	1.5 M	PREMIUM GALV. FOR CFB TO BLOCK	CONCRETE
5323HPST	1-1/4" (32mm)	SMOOTH STEP	1.5 M	3/4" CFB & PLYWOOD TO 3/16" STEEL	STEEL
5383HP	1-1/2" (38mm)	SMOOTH	1.5 M	PLYWOOD	CONCRETE
5384HP	1-1/2" (38mm)	HELICAL	1.5 M	PLYWOOD	STEEL
5454HP	1-3/4" (44mm)	HELICAL	1.5 M	3/4" CFB & PLYWOOD TO 3/16" STEEL	STEEL
5503HP	2" (51mm)	SMOOTH	1.5 M	2X4 TO RED IRON STEEL CFB TO FOAM TO CONCRETE	STEEL CONCRETE
5503HPST	2" (51mm)	SMOOTH STEP	1.5 M	2X4 TO RED IRON STEEL CFB TO FOAM TO CONCRETE	STEEL CONCRETE
5573HP	2-1/4" (57mm)	SMOOTH	1 M	SLEEPER / DIM. LUMBER	CONCRETE
5573HPG	2-1/4" (57mm)	SMOOTH	1 M	ACQ 2x4 TO RED IRON STEEL & CONCRETE	STEEL CONCRETE
5633HPG	2-1/2" (63mm)	SMOOTH	1 M	ACQ 2x4 TO RED IRON STEEL & CONCRETE	CONCRETE

## Tool Features and Accessories



Yellow Outlets  
Regular Pressure



Orange Outlets  
High Pressure



**400 PSI Compressor**  
High pressure compressor designed to operate High Pressure tools. (AKH1050)



### Air Hose and Fittings

High pressure hose and fittings are designed exclusively for High Pressure tools. 100 ft./30 mm High Pressure Hose (KHL100FTx30)



Wide range of fastener length with adjustable magazine plate. 1" to 2-1/2" pin accommodation



HN120 Swivel  
Hose Fitting

Aeromsmith Fastening Systems  
5621 Dividend Road, Indianapolis, IN 46241  
Ph: 317.243.5959 Fax: 317.390.6980  
Email: info@AeromsmithFastening.com  
www.AeromsmithFastening.com

Member of  
Steel Framing Alliance™

Aeromsmith Fastening Systems (Aeromsmith) does not practice structural engineering, or architectural / building design, and is not responsible for the recommendation or use of its products in situations where a professional or certified opinion is required. It is the responsibility of the end user to comply with all local building codes, project design specifications, and good building practices. For the use of building professionals, Aeromsmith does provide third party evaluation reports and engineered test data performed to recognized protocols.