




Fully Automatic Tape Sealer
Up to 25 cases per minute




RSC Case
The BEL 252
seals RSC
cases.




Fully Automatic Case Taper



Squareness Assured
BEL's innovative and powerful Uni-Drive system synchronizes conveyor belt speed, eliminating case skew, so that cases leave the machine squarely taped.



Ultra Safe Flap Folder
Snap Folder flap-folding technology safeguards personnel by eliminating the traditional "flap kicker," which can cause serious injury and the need for expensive machine guarding.



Superior Tape Application
The BEL 252 is equipped with state-of-the-art DEKKA High Performance stainless steel tape heads that are easily loaded in or out of the machine in 30 seconds or less.



Easy Case Change
The BEL 252 is user-friendly, enabling the operator to make box size changes from either side of the machine quickly and easily in 30 seconds or less.

Case Sealer
BEL 252

BEL 252 Fully Automatic Top and Bottom Case Taper

BEL 252 Features

- BEL's revolutionary Snap Folder design safely folds flaps and eliminates the use of dangerous flap kickers, which can cause injuries.
- The paint-free finish guards against contamination from flaking or peeling paint.
- Magnetic motor starter protects operator from accidental re-starts after a power interruption and protects motor against power overload.
- Uni-Drive squaring mechanism means more presentable cases.
- Quick, open-top pulleys enable drive belts to be replaced in minutes reducing maintenance and downtime.
- Automatic case indexing with adjustable timer for steady flow and throughput.
- Standard DEKKA 22 Stainless Steel 2" tape heads and optional DEKKA 3" tape heads are available.

Complete Solution



BEL 505 Case Former

The BEL 505 improves efficiency and ergonomics. Inserting a case into the BEL 505 results in all four bottom flaps being automatically folded, leaving hands free to pack.



Wexxar WF20 and WF30 Case Former

The WF20 and WF30 fully automatic case formers continuously and effortlessly open and form cases, presenting them ready for packing.



S10 Weigh Scale


Machines can be equipped with weigh scales to allow the operator to monitor or weigh products being loaded before case sealing.

BEL 252 Specifications

Case Size Range	Length	Width	Height
Minimum	8" 203 mm	6" 152 mm	4 1/2" 114 mm
Maximum	22" 559 mm	15" 381 mm	16" 406 mm
Infeed/Outfeed Height (with adjustable foot pads)			
Minimum	23 1/2" (597 mm)		
Maximum	32" (813 mm)		
Machine Speed: Up to 25 cases per minute depending on box size. Oversize model available: consult factory for case size ranges.			

Specifications are subject to change without notice.

How the BEL 252 Works



The BEL 252 seals RSC cases.




1 Quick Change Handle

A quick three step size change with simple hand wheel and clamp adjustments, enable the BEL 252 to seal a wide range of case sizes.



2 Snap Folder

Cases are automatically folded with BEL's safe snap folding technology. This protects personnel by eliminating the traditional "flap kicker".



3 Top and Bottom Sealed

Superior case sealing performance is achieved with its quality tape application. The BEL 252 comes standard with DEKKA tape heads.



Wexxar Packaging Inc.
10101 Nordel Court
Delta, BC Canada
V4G 1J8

Phone: 604-930-9300
Fax: 604-930-9368
Email: sales@wexxar.com
Web: www.wexxar.com

a division of Pro Mach 

Backed by Wexxar's warranty and experienced, nationwide service team.