

HIGHEST HOLDING POWER IN THE INDUSTRY

CARTON SEALING TAPE

HP SERIES

Nobody notices carton seals unless something goes wrong. Carton sealing tape should be strong enough to hold and tough enough to endure shipping abuse, yet release smoothly from the roll and deliver consistent tension in demanding high speed applications. A tall order? Not for the HP Series, only from Shurtape.

No other tape holds like Shurtape HP Series. From manual applications using hand rolls to automated packaging lines where our machine-length rolls maximize throughput, saving time and labor – HP performs right down to the core.

Shipping conditions may change, but our packaging tape performs consistently. Constructed of biaxially-oriented polypropylene (BOPP) film with our proprietary hot melt adhesive formula, HP Series has unequaled holding power, uncompromising strength, and superior moisture resistance, roll after roll.



HIGHEST HOLDING POWER IN THE INDUSTRY

CARTON SEALING TAPE



Time to Upgrade Your Tape Heads?

Are your tape heads hard-to-load and wear out before they should? Try our tape head program. With a signed agreement to purchase any HP machine-length product we'll give you a durable, stainless steel SP tape head. Our SP tape head, with one-touch adjustment, is easy to load, easy to clean, and ready to work.

Contact your Shurtape sales representative for more information.

REGIONAL SALES OFFICES & DISTRIBUTION CENTERS

North Carolina

Catawba Industrial Place
3389 Catawba Industrial Place
Catawba, NC 28609

tel: (828) 322-2700
(888) 442-8273
fax: (828) 322-4029

Arizona

First Commerce Center
725 N 73rd Avenue, Suite 112
Phoenix, AZ 85043

tel: (623) 463-5886
(800) 342-8273
fax: (623) 463-5809

INTERNATIONAL SALES OFFICES & DISTRIBUTION CENTERS

US Corporate Headquarters

Shurtape Technologies, LLC
1712 8th Street Drive SE
PO Box 1530
Hickory, NC 28603 USA

tel: (828) 322-2700
(888) 442-8273
fax: (828) 322-4029
www.shurtape.com

Canada

Shurtape Technologies Co.
615 Bowes Road
Concord, ON
Canada L4K 1J5

tel: (905) 669-4881
(800) 463-8273
fax: (905) 669-2330

Europe

Kip GmbH
Schlavenhorst 9 (Industriepark)
D-46395 Bocholt, Germany

tel: +49 2871-23466-27
fax: +49 2871-23466-32
contact: Monica Ptok
www.kip-tape.com

United Arab Emirates

Shurtape Ved Ltd.
PO Box 6137
Dubai, United Arab Emirates

tel: +971 (4) 880-7008
fax: +971 (4) 880-9242
email: shurtape@emirates.net.ae

Mexico

Shurtape México, S. de R.L. de C.V.
Paseo de la Constitución #11
Fracc. Ind. Peñuelas
C.P. 76148, Querétaro, Qro
México

tel: +52 (44) 2220-6367
fax: +52 (44) 2220-6366
email: shurtmex@prodigy.net.mx

Peru

Shurtape Peru S.A.
Av. Minería 141-155
Urb. Fundo Puente-Santa Anita
43 Lima, Peru

tel: +51 (1) 362-8212
fax: +51 (1) 362-0476
email: ventas@shurtapeperu.com

China

Shurtape Technologies (Shanghai) Co. Ltd.
No. 175 Block A
West Maojing Road
Songjiang EPZ Industrial Zone
Shanghai 201611
P.R. China

tel: +86 (21) 5774-9500
fax: +86 (21) 5574-9599
contact: Jason Chen
email: info@shurtape.com.cn

China

Shurtape Technologies (Changshu) Co., Ltd.
No. 301 Yintong Road
Changshu Southeast Economic
Development Zone
Changshu, 215500
Jiangsu, China

tel: +86 (512) 5235-9500
fax: +86 (512) 5235-9528
email: info@shurtape.com.cn

Shurtape®

www.shurtape.com 1.888.442.TAPE

ISO 9001 CERTIFIED QUALITY SYSTEM

©2012 Shurtape Technologies, LLC
"Shurtape" is a registered trademark of Shurtape Technologies, LLC.
Printed in USA on recycled paper.
Form #SS-HPSeries-03/29/2012-P2M

Shurtape®

www.shurtape.com 1.888.442.TAPE

HP SERIES

A TAPE FOR EVERY CARTON SEALING NEED

HP 100



HP 100 is designed for lightweight cartons exposed to minimal stress in shipping and handling. It sticks instantly to the carton yet unwinds easily from machine and hand rolls. It is an economical solution that performs consistently—making it a great value.

Tensile Strength	21 lbs/in width
Adhesion to Stainless Steel	42 oz/in width
Thickness	1.6 mils
Holding Power to Fiberboard (min)	10,000
Application Temperature Range	35° - 110° F
Service Temperature Range	20° - 150° F

HP 200



For superior performance in automated industrial carton sealing processes, this instant seal production tape is ideal for sealing medium weight cartons in most manufacturing and shipping environments. Now available in transparent colors for inventory identification.

Tensile Strength	27 lbs/in width
Adhesion to Stainless Steel	44 oz/in width
Thickness	1.9 mils
Holding Power to Fiberboard (min)	15,000
Application Temperature Range	35° - 110° F
Service Temperature Range	20° - 150° F

HP 232



This purpose-built tape securely seals cartons in cold-temperature environments such as produce packaging, meat and poultry processing, dairy facilities and cold weather moving and storage. It instantly sticks and stays in sub-freezing temperatures.

Tensile Strength	27 lbs/in width
Adhesion to Stainless Steel	30 oz/in width
Thickness	1.9 mils
Holding Power to Fiberboard (min)	10,000
Application Temperature Range	20° - 75° F
Service Temperature Range	-20° - 100° F

HP 240/250



HP 240 and HP 250 security carton sealing tapes are lock printed--providing a durable message that will not rub off or degrade the adhesive. Two standard messages are in-stock: STOP - If Seal Is Broken; SECURITY TAPE. Custom messages (your company's name or marketing message) are available on HP 250 with adequate lead times and a minimum order.

Tensile Strength	27 lbs/in width
Adhesion to Stainless Steel	44 oz/in width
Thickness	1.9 mils
Holding Power to Fiberboard (min)	15,000
Application Temperature Range	35° - 110° F
Service Temperature Range	20° - 150° F

HP 300



This instant seal, performance grade tape performs consistently in a wide variety of applications and environments. It's best for sealing medium-weight cartons subjected to increased handling stress.

Tensile Strength	30 lbs/in width
Adhesion to Stainless Steel	47 oz/in width
Thickness	2.2 mils
Holding Power to Fiberboard (min)	20,000
Application Temperature Range	35° - 110° F
Service Temperature Range	20° - 150° F

HP 400



Large and heavy content cartons in automated or manual applications are no match for this instant seal high-performance tape. This tape is designed for high-stress, extreme-handling conditions. When high-speed, critical-closure production lines need secure seals, rely on HP 400.

Tensile Strength	33 lbs/in width
Adhesion to Stainless Steel	54 oz/in width
Thickness	2.5 mils
Holding Power to Fiberboard (min)	25,000
Application Temperature Range	35° - 110° F
Service Temperature Range	20° - 150° F

HP 500



Our premium carton sealing tape, HP 500, is designed for heavy-duty cartons. It performs consistently on demanding packaging lines and holds strong under rigorous shipping conditions. It seals instantly to corrugated cartons, paper, film and a variety of other substrates—even cartons with high recycled content.

Tensile Strength	42 lbs/in width
Adhesion to Stainless Steel	58 oz/in width
Thickness	3.0 mils
Holding Power to Fiberboard (min)	30,000
Application Temperature Range	35° - 110° F
Service Temperature Range	20° - 150° F

HP 800



Our thickest, toughest carton sealing tape yet. It's purpose-built to seal the bottoms of heavy-duty double and triple-walled cartons. HP 800 is extremely strong with an abrasion-resistant polyester film. It will hold strong in the most extreme handling conditions and meets the ASTM D5486 Type II standard.

Tensile Strength	54 lbs/in width
Adhesion to Stainless Steel	95 oz/in width
Thickness	3.4 mils
Holding Power to Fiberboard (min)	35,000
Application Temperature Range	35° - 110° F
Service Temperature Range	20° - 150° F