

PRHR

Pneumatic Push-type Combination Tool for Steel Strapping



Easy to operate

The PRHR's ergonomic design makes it easy to maneuver when suspended, helping to reduce operator fatigue. Simple one-lever operation allows fast tensioning, sealing and cutoff.

Simple to maintain

The PRHR features minimal wear parts and a feedwheel that can be replaced in minutes.

Versatile

It is ideal for angular and irregularly-shaped products.

Durable

All metal and alloy parts provide long-lasting, low-maintenance operation.

Specifications

Strapping: For use with Apex or Magnus® steel strapping and Signode seals:

PRHR-34: 3/4" (19 mm) x .025"-.031" (0.64 mm – 0.79 mm) & 34HOC Seals

PRHR-114: 1-1/4" (32 mm) x 0.25"-.031" (0.64 mm – 0.79 mm) & 114P Seals

PRHR-1444: 1-1/4" (32 mm) x .035" - .044" (.89 mm – 1.12 mm) & 114P/114HD Seals

Tension: Up to 1,600 lbs. (7 117 N)

Joint type: Double reverse notch

Weight: 29 lbs. (13.2 kg)

Part number: 424234 - PRHR-34

423570 - PRHR-114

429384 - PRHR-1444

For Sales & Service:
R.V. Evans Company
800-252-5894
www.rvevans.com

 **SIGNODE®**

3650 West Lake Avenue
Glenview, IL 60026
1-800-323-2464
www.signode.com