

Aerosmith Fastening Systems

VERSAPINTM FASTENING SYSTEM

ST565

Features

- † Lightweight - only 4.8 lbs
- † Depth of Drive Adjustment
- † 360° adjustable exhaust deflector
- † Uses Aerosmith flat wire welded fasteners and plastic sheet collated fasteners. No adjustments necessary
- † Anti-Double fire mechanism
- † Trigger Lock to prevent accidental firing
- † Anti-Skid pad
- † Shock absorbing comfort rubber handle
- † Belt Clip
- † Comes with plastic carrying case



Applications

- † Plywood to Steel 14 – 20 ga (68-33 mil)
- † Exterior Gypsum to Steel 14 – 20 ga (68-33 mil)
- † Cement Fiber Board to Steel 14 – 20 ga (68-33 mil)
- † Steel to Steel 14 – 20 ga (68-33 mil)
- † Stucco Lath Applications 14 – 20 ga (68 - 33 mil)

Specifications

Height	12 9/16" (320 mm)
Width	5-1/8" (130 mm)
Length	10-3/4" (273 mm)
Weight	4.8 lbs (2.2 kgs)
Recommended Operating Pressure	70-120 psi (4.9-8.3 bar)
Loading Capacity	Up to 250 fasteners

Fastener Specifications

Wire Welded Coil Fasteners	1-3/8" – 2-1/2" (45-63 mm)
Plastic Sheet Collated Coil Fasteners	1-3/8" – 1-1/2" (45-38mm)
Shank Diameter	.092" – .102" (2.3-2.6 mm)
Head Diameter	.197" - .252" (5.0 – 6.4 mm)
Recommended Fasteners	Aerosmith Helical, Gripshank and Gripshank SuperSharp
Accessories	Magnetic washer adapter (UNM565)