

POSITIVE PLACEMENT® METAL CONNECTOR NAILER



Paslode® is proud to introduce the latest customer-backed innovation in Positive Placement® technology. The NEW! Paslode® 2½" Positive Placement® Metal Connecting System is designed to provide installers the optimal way for fastening structural hardware to wood structures. The pneumatic system significantly reduces installation time, allowing jobs to be completed faster and reducing the need for additional labor.



Model/Part Number PF250S-PP/511800

Specifications

Nail Range: 1 ½" – 2 ½" Positive Placement® Nails

Nail Diameter: .131" - .162" Positive Placement® Nails

Nail Angle: 30 Degrees

Nail Capacity: 2 Strips of Nails Plus Lockout (55 – 60 Nails)

Weight: 7.8 lbs.

Dimensions: 17.4" L x 14" H x 3.7" W

Operating Pressure p.s.i. (Bar): 80 – 120 psi (5.5 – 8.3)

Air Requirement/100 p.s.i. (6.9 bar): .079/cycle

Warranty

90-Day Limited: Wear Components

6-Month Limited: Magazine Components

1-year Limited: Housing and Cap Components

Versatile: Drives 1 ½" and 2 ½" nails.

Dependable: Drive nails consistently to maximize productivity and efficiency.

Lightweight and Compact: Reduces fatigue and increases maneuverability.

Accurate: Probing tip guides nails into hardware holes.

Features and Benefits

Durable – Designed for use in tough jobsite conditions.

Reliable – Drives consistently when using Paslode® Positive Placement® nails. Low maintenance.

Probing Tip – Accurately locates hardware holes quickly – Work Faster.

Quick Release Magazine – Provides access to the nail raceway for faster service times while reducing the potential for damaging components – Saves Time and Money.

Left/Right Handed Belt Hook – Belt hook can be placed on either side.

2-Step Loading – Easily loads 2-strips – Increases Productivity.

Thumbwheel Depth of Drive – Changes nail depth in an instant.

Auto-Bias Lever – Automatically adjusts to drive 1 ½" and 2 ½" fasteners.

R.V. Evans Company
www.rvevans.com
1-800-489-1107