

ANY TEMPERATURE, ANY APPLICATION

ACRYLIC CARTON SEALING TAPE

AP SERIES

Our six grades of acrylic carton sealing tapes are perfect for any job, whether you need strength for bulky packages or a rapid initial bond on recycled paperboard.

Each tape also offers many of the same qualities: The ability to withstand extreme temperatures, so your package stays sealed no matter how cold it is when you send it, or how hot it is where the package arrives. The UV-resistance that will protect your boxes and labels from yellowing. And the value that comes from stretching a dollar without sacrificing long-term performance.

- > Designed for all kinds of applications, from heavy duty to light duty to cartons with highly finished graphics.
- > Holds strong in temperatures ranging from -20° to 180° F.
- > Protects labels and printed surfaces from weather and handling.
- > Excellent aging characteristics for long-lasting performance.
- > Thickness ranges from 1.6 mils to 2.5 mils.



Shurtape®

www.shurtape.com 1.888.442.TAPE

ANY TEMPERATURE, ANY APPLICATION

ACRYLIC CARTON SEALING TAPE



AP 015



- Protects shipping labels and other printed surfaces from weather and handling.
- High Clarity
- Won't yellow
- UV Resistant

Tensile Strength	20 lbs/in width
Adhesion to Stainless Steel	19 oz/in width
Thickness	1.6 mils
Elongation	150 %
Application Temperature Range	20° to 110° F
Service Temperature Range	-20° to 180° F



AP 101



- Light duty packaging in extreme temps.
- Provides flexibility and strength.
- Excellent aging characteristics for long-term use.
- Clear, UV-resistance and non-yellowing features.
- High clarity and low odor.

Tensile Strength	20 lbs/in width
Adhesion to Stainless Steel	18 oz/in width
Thickness	1.6 mils
Elongation	150 %
Application Temperature Range	20° to 110° F
Service Temperature Range	-20° to 180° F



AP 201



- Automated or manual sealing of light- to medium-weight cartons.
- High clarity and low odor.
- Performs in extreme temps.
- Clear, UV-resistance and non-yellowing features.

Tensile Strength	24 lbs/in width
Adhesion to Stainless Steel	22 oz/in width
Thickness	2 mils
Elongation	150 %
Application Temperature Range	20° to 110° F
Service Temperature Range	-20° to 180° F




AP 301



- Automated or manual sealing of medium weight cartons.
- High clarity and low odor.
- Clear, UV-resistance and non-yellowing features.
- Excellent aging characteristics for long-term use.
- Performs well in extreme temps.

Tensile Strength	27 lbs/in width
Adhesion to Stainless Steel	25 oz/in width
Thickness	2.2 mils
Elongation	150 %
Application Temperature Range	20° to 110° F
Service Temperature Range	-20° to 180° F



AP 401



- Automated or manual carton sealing under rough handling and load stress.
- High clarity and low odor.
- Clear, UV-resistance and non-yellowing features.
- Excellent aging characteristics for long-term use.
- Performs well in extreme temps.

Tensile Strength	30 lbs/in width
Adhesion to Stainless Steel	27 oz/in width
Thickness	2.5 mils
Elongation	150 %
Application Temperature Range	20° to 110° F
Service Temperature Range	-20° to 180° F

ISO 9001 CERTIFIED QUALITY SYSTEM
 © 2012 Shurtape Technologies, LLC
 "Shurtape" is a registered trademark of Shurtape Technologies, LLC.
 ♻️ Printed in USA on recycled paper.
 Form #SS-APSeries-04/04/2012-P2M

Shurtape®

www.shurtape.com 1.888.442.TAPE