



DEKKA Cadet

This is the standard tape head for applying 2" wide tape. The Cadet series heads provide consistent application performance for most low to mid speed tape sealing lines.

Specifications:

- 2" Tape
- 2.325" to 2.75" Tab Length
- Runs to 80 to 120 fpm*

INCLUDED FEATURES:

- Construction** DEKKA Cadet tape heads are constructed using modern laser cutting technology in zinc plated and powder-coated steel.
- Easy to Load** With DEKKA's open side frame design, tape loading is simple and easy. Loading can be done in 30 seconds or less without removing the tape head or taking the machine out of adjustment. Reduces down time and costly production delays.
- Exclusive No Break Tape Advance** In conventional tape heads, feed rolls pull tape along its edges where breaks actually occur. DEKKA's exclusive No Break Tape system advances the tape along its centerline, avoiding edge stress and helping to prevent tape breaks. Eliminates delays and lost production.
- External Tape Guide System** DEKKA's external tape guide physically holds tape ends in place unaffected by external drafts or loss of static attraction to the wipe down roller. The guide remains free from troublesome adhesive build-up. Taping case tops or bottoms, DEKKA tape heads reliably seal case after case, avoiding costly reprocessing of untaped cases.
- Easily Adjustable Roller Tension Spring** Adjust main spring tension by selecting one of four preset leverage points. Adjustments are unaffected by vibration and shock.
- High Quality Molded Wipe Down Rollers** Many tape heads are fitted with separate roller sleeves requiring frequent replacements due to surface breaks and splits. DEKKA's polyurethane wipe down rollers are molded in one piece. The result is tougher, longer lasting rollers requiring less maintenance.
- Expands Your Tape Buying Power** DEKKA tape heads are designed to provide superior performance on all brands of tape, from budget price to premium grades, which helps minimize tape cost.