



Fully-automatic high-performance side sealer
with continuous motion sealing system

Servo Jet 400 series

Smart Technology for more flexibility

Continuous motion side sealers for reliable and troublefree high-performance packaging. The innovative linkage of decentralized servo drives with a PC-based ELAU MAX 4 (Gen 3) control system results in high performance with an attractive pricing.

Servo Jet 400/80 reaches a top performance of approx. 80 packs/min., Servo Jet 400/120 goes up to 120 packs/min., and the Servo Jet 400/170 peaks at approx. 170 packs/min. A colour Touchpanel with product data memory for various products allows quick changeovers by simply calling up the needed data from the database.



Kallfass
Verpackungsmaschinen

Results count.


Facts, data, figures

Technical data	Servo Jet 400 / 80 · 400 / 120 · 400 / 170
Min. / max. product length:	80 mm / upon request
Min. / max. product width:	50 mm / 400 mm
Sealing systems (cross sealer):	Special coating, permanently heated, maintenance free, fast and easy exchangeable sealing ledge in different profiles for high-quality seals
Width of cross seal bar:	450 mm
Max. clearance height of cross sealer:	max. 200 mm
Operator interface:	colour Touchpanel, ELAU
Variable speeds transport conveyor:	depending on model: from max. 35 m / min. up to max. 58 m / min.
Film reel width:	max. 600 mm (centre-folded film), optional also flat film
Film reel outside diameter:	max. 400 mm
Min. / max. width of film scrap:	15 mm / 100 mm
Power supply:	400 volts, 50 Hz, with protective earth conductor without power cord and plug
Working height:	850 (adjustable \pm 50 mm)
Position of control panel and operating side:	left hand side in working direction
Position of control cabinet:	right hand side in working direction (rear side of machine)
Colour:	Kalfass anthracite

Selected advantages

- Continuous motion seal bar
- Continuous packaging process without product stop
- Continuous side sealing system
- Film tear and film end control
- Infinitely variable conveyor speed
- Automatic and power driven waste film take-up winder
- Adjustable working height
- Compressed air not required

Machine dimensions (approx. in mm):



Kalfass
Verpackungsmaschinen

Kalfass Verpackungsmaschinen GmbH
Siemensstrasse 8 · 72622 Nürtingen-Zizishausen · Germany
Phone +49/7022/607-0 · Fax +49/7022/607-200
info@kalfass.com · www.kalfass.com

